

TANKS

WATER SPRINKLING AND FLUSHING

THE WIDEST RANGE
OF STREET CLEANING
EQUIPMENT



ROS ROCA

Environmental
technology.



Water Sprinkling and Flushing Tanks.

The Ros Roca tanks are renowned for their efficiency and versatility both for street sprinkling and flushing as well as for use as auxiliary fire-tenders.

There is also available a large range of options in order to satisfy the customer requirements.



-Soundproof auxiliary engine



-Joystick control



-Rear reel



-Side sprinkler jets and flushing jets.



-Side sprinkling



-Automatic control system of the water flow **VARIAQUA**

SPECIFICATIONS

Capacities

From 6.000 to 15.000 litres (depending on the options and the chassis).

Materials

Stainless steel.

Carbon steel with internal lining of epoxy coat (optional).

Control panel

Pneumatic.

Joystick control by PLC.

Pump driving

Gear box mounted or soundproof auxiliary engine.

Hydrostatic transmission (optional).

Pressure pump

30 m³/h - 6 bar.

Multistage centrifugal pump 15m³/h - 15 bar (optional).

Outlets of the pressure

Right side outlet.

Second and third pressure outlet (optional).

Sprinkler jets

2 sprinkler jets.

Flushing jets

In the front, 1 set of 2 nozzles with pneumatic orientation.

Second kit of nozzles (optional).

Front flushing jets with automatic regulation system of the water flow **VARIAQUA** (optional).

Side flushing jets (optional).

Under chassis flushing jets (optional).

Sprinkling bars

Crossing bars (optional).

Rear bars (optional).

Sprinkler bars

Sprinkler bars between crossbars (optional).

Manual, hydraulic and electrical operation.

Watering pole

Guided water pole with aluminium fairing.

Rear locker

Locker for tools (optional).

Finishing

Stainless steel scale.

Painting (optional).

Others optional

Flow control .

Suction circuit with a high capacity filter.

MODEL	NO SOUNDPROOF			SOUNDPROOF		
	G.V.W. CHASSIS	WHEELBASE	PAYLOAD*	G.V.W. CHASSIS	WHEELBASE	PAYLOAD*
6SA				13/14 Tm	3.100mm	5.000/6.000 L
7SA	13/14 Tm	3.100mm	6.500/6.500 L	15/16 Tm	3.500mm	7.000 L/8.000 L
9LA	15/16 Tm	3.100mm	8.000/9.000 L	18 Tm	4.100mm	9.000 L
10SA	18 Tm	3.800mm	10.000 L			
15LA	26 Tm	3.200+1.395mm	15.000 L	26 Tm	4.200+1.395mm	14.000 L

*Approximate legal payload depending on the optional choice.



The Quality management system is applied to the design, production and sales of urban and industrial cleaning and sewerage systems.

Specifications subject to modification without prior notice.
The illustrations may not correspond to standard versions of the units.



ROS ROCA S.A.

www.rosroca.com

Av. Cervera, s/n.
Ph.: +34 973 50 81 08 / 09
Fax: +34 973 50 81 32
25300 TÀRREGA (LLEIDA) SPAIN

e-mail: export@rosroca.com